





QUALITY, DURABILITY, VALUE

Tapered Nestable Roll-Off Container

Standard Specifications

- 3 Types to choose from:
 - o Standard all 12 GA Construction.
 - o Heavy Duty all 10 GA Construction.
 - o Heavy Duty 10 GA Construction with 7 GA floor.
- 4"x 4" Structural tubing top headers.
- "Dog House" style hook-up with heavy duty snatch hook.
- 4"x 6" Nose rollers with grease fittings and 1 1/2" axles.
- 6"x 2" Structural tubing main rails with gusseted crossmembers.
- 1-Piece door (non watertight).
- Safety chain with hooks for holding doors open.
- Heavy Duty 9" x 7 GA structural tubing door hinge posts.
- 3" Structural channel floor members spaced at 16" centerlines.
- Front and rear ladders.
- Tarp hooks at approx. 4' centerlines.
- Mitered corners to protect tarps.
- 8"x 8" Stationary steel wheels, rear with grease fittings.
- Interior and exterior coated with rust inhibitive alkyd primer.
- Exterior painted your choice of standard color with alkyd enamel paint. Some colors may be extra.

8613 Mulberry Avenue Fontana, CA 92335 **800.635.8335**

Bottom coated with automotive underseal.



Tapered Nestable Roll-Off Container





SIZE

CUBIC YDS

10' x 4'	9.4 YDS
14' x 3'	9.8 YDS
16' x 4'	15.2 YDS
18' x 3-1/2'	14.8 YDS
18' x 4'	17.1 YDS
20' x 4'	19.1 YDS
20' x 7'	34.6 YDS
22' x 4'	21.0 YDS
22' x 5'	26.7 YDS
22' x 5-1/2'	29.6 YDS
22' x 7'	38.1 YDS
24' x 5-1/2'	32.3 YDS
22' x 7'	38.1 YDS

8613 Mulberry Avenue Fontana, CA 92335 800.635.8335



