

Pitch Top Container



QUALITY, DURABILITY, VALUE

Standard Specifications

- Plastic lids.
- 14 GA construction with flanged corners and horizontal "V" groove ribs front, back and bottom.
- 12 GA interlocking banding.
- 11 GA 4"x 8" full length gusseted fork channels - on ends reinforced at pick-up points (2" recess or flush front & rear). 1 1/2, 2 cu. yd. with 4 gussets per channel, 3 cu. yd. with 6 gussets per channel, 4 cu. yd. with 8 gussets per channel.
- Channels available on bottom with 4 gussets per channel.
- Zinc plated lid rod with 90 degree bend and nylon lock nut.
- Lid holders to hold lids open.
- Lid ears to accommodate plastic or steel lids.
- 6" Roller bearing rubber swivel casters with grease fittings (450 lb. capacity each).
- 10 GA casterplates with flange for strength.
- Interior coated with automotive underseal or rust inhibitive alkyd primer.
- Exterior (including bottom) painted your choice of standard color with alkyd enamel paint. Some colors may be extra.

Pitch Top Front Load Container



Dimensions and Drawing

PRODUCT #	SIZE	FRONT HEIGHT	BACK HEIGHT	WIDTH	LENGTH
		A*	B*	C	D**
9001	1.5 YD	29.5"	34.5"	29.5"	72"
9002	2 YD	34.5"	41.5"	34.5"	72"
9005	3 YD	41.5"	50.5"	41.5"	72"
9007	4 YD	46"	57"	50.5"	72"

* Casters add 8" to height

** End loader = 80"

