

Radius Bottom Trash Roll-Off Container



QUALITY, DURABILITY, VALUE

Standard Specifications

- Available in 10, 15, 20, 30 & 40 cu yd.
- 12 GA construction (10 cu yd = 10 GA construction with 7 GA floor) with 15" radius on sides.
- 3"x 3" (10 GA) structural tubing top headers.
- "Dog House" style hook-up with heavy duty snatch hook and 4"x 6" nose rollers with grease fittings and 1 1/2" axles.
- 6" Structural channel gusseted main rails.
- 3" Structural channel floor members at 24" centerlines (10 cu yd at 16" centerlines).
- 12 GA double doors with 1" lock bars (1' taller than sides) and safety chain with hooks for holding doors open.
- 2"x 3" Structural tubing door hinge posts.
- Tarp hooks at approximately 4' centerlines.
- Formed ladder with gussets for added strength on front driver's side (OSHA compliant).
- Mitered corners to protect tarps.
- 10"x 8" Stationary steel wheels with grease fittings. Stand also available.
- Interior and exterior coated with rust inhibitive alkyd primer.
- Exterior painted your choice of standard color with alkyd enamel paint. Some colors may be extra.
- Bottom coated with automotive underseal.

Radius Bottom Roll-Off Container

Dimensions



Size (A x B)	Cubic Yards
12' x 3'	9.5 YDS
12' x 4.5'	14.4 YDS
14' x 4'	14.9 YDS
16' x 4'	17.1 YDS
18' x 4'	19.2 YDS
18' x 5'	24.1 YDS
18' x 6'	29.1 YDS
22' x 3.5'	20.6 YDS
22' x 4'	23.6 YDS
22' x 5'	29.6 YDS
22' x 6'	35.6 YDS
22' x 6.5'	38.6 YDS
22' x 8'	47.7 YDS

