

Radius Bottom Sludge Roll-Off Container



QUALITY, DURABILITY, VALUE

Standard Specifications

- 12 GA or 10 GA construction.
- 96" Wide outside - 90" wide inside.
- 15" Radius at front and sides.
- 3"x 3" (7 GA) structural tubing headers.
- 3"x 3" (10 GA) structural tubing floor sill.
- Two front vertical center posts 3" structural channel.
- Side posts 3"x 3" (7 GA) structural tubing. 4' and lower have one vertical center post. 4 1/2' and taller have one vertical center post and one center horizontal member.
- 6" Structural channel gusseted main rails.
- Double end hook-up, 4"x 6" nose rollers with grease fittings and 1 1/2" axles.
- Guaranteed watertight with one piece flush rear door (top or side hinged).
- 5/16" Liner hooks on all four sides 1 1/2" down.
- 12 3/4" x 12 3/4" Placard brackets on all four sides.
- Ladder with gussets on front driver's side with interior exit ladder. OSHA compliant.
- Inspection ladder on driver's side center.
- Mitered corners to protect tarps.
- 8"x 8" Stationary steel wheels with grease fittings - front and rear.
- Interior and exterior coated with rust inhibitive alkyd primer.
- Exterior painted your choice of standard color with alkyd enamel paint with hardener. Some colors may be extra.
- Bottom coated with automotive underseal.
- Shown with optional Ultra EZ-Flip Plastic Roof.