

## Vacuum Roll-Off Container



### RUGGED, DURABLE, RELIABLE

#### Standard Specifications

- 18 cu yd (16' X 5') and 25 cu yd (22' X 5') standard sizes.
- Steel construction: 3/16" floor, 1/4" sides, and 5/16" roof.
- 6" x 2 1/4" Structural tube main rails with gussets on every crossmember.
- Structural tubing center belly band.
- "Dog House" with 4" x 6" nose rollers (1 1/2" axle) front.
- Double end hook-up.
- 3" Floor baffle.
- Domed hatch cover in roof with seal and access ladder (2 each on 25 cu yd).
- 2-8" Inlet/outlet flanges.
- 8" Steel boggie wheels front and rear, wheel locks front.
- 3" Structural channel crossmembers on 16" centerlines.
- 1-Piece watertight rear door, side hinged with heavy-duty neoprene door seal and heavy-duty hinges.
- Hydro static tested to top.
- Optional lift eyes.
- Can be made compatible with all types of roll-off trucks.
- Interior bare metal.
- Exterior one coat of rust inhibitive primer and painted your choice of standard color with alkyd enamel paint. Some colors may be extra.
- Bottom coated with automotive underseal.

14620 ARMINTA STREET  
VAN NUYS, CALIFORNIA 91402  
800.635.8335 TOLL FREE  
818.787.6312 FAX