

## Flat Top Front Load Container



### QUALITY, DURABILITY, VALUE

#### Standard Specifications

- Plastic lids.
- 14 GA construction with flanged corners and horizontal "V" groove ribs front, back and bottom.
- 12 GA interlocking banding.
- 11 GA 4"x 8" full length gusseted fork channels on ends reinforced at pick-up points (2" recess or flush front & rear). 1 1/2, 2 cu yd with 4 gussets per channel, 3 cu yd with 6 gussets per channel, 4 cu yd with 8 gussets per channel.
- Channels available on bottom with 4 gussets per channel.
- Zinc plated lid rod with 90 degree bend and nylon lock nut.
- 1/2" Lid rods with lock washers at ends.
- Lid holders to hold lids open.
- Lid ears to accommodate plastic or steel lids.
- 6" Roller bearing rubber swivel casters with grease fittings (450 lb. capacity each).
- 10 GA casterplates with flange for strength.
- Interior coated with automotive underseal or rust inhibitive alkyd primer.
- Exterior (including bottom) painted your choice of standard color with alkyd enamel paint. Some colors may be extra.

## Flat Top Front Load Container



### Dimensions and Drawing

PRODUCT #	SIZE	HEIGHT	WIDTH	LENGTH	CUBIC YARDS
		A*	B	C**	
10500***	1 YD 49"	35"	28"	49"	1.03
10501***	1 YD 60"	30"	26"	60"	1.00
9095	1 YD 72"	28"	24"	72"	1.04
10504	2 YD FH	34.5"	34.5"	72"	1.84
9003	2 YD IH	38"	34.5"	72"	2.02
9004	2 YD BH	41.5"	34.5"	72"	2.21
10507	3 YD FH	41.5"	41.5"	72"	2.66
10509	3 YD IH	46"	41.5"	72"	2.95
9006	3 YD BH	50.5"	41.5"	72"	3.23
10512	4 YD FH	46"	50.5"	72"	3.58
9008	4 YD IH	50.5"	50.5"	72"	3.94
10514	4 YD BH	56.5"	50.5"	72"	4.40

\*Casters add 8" to height

\*\*End Loaders = 80"

\*\*\*Bottom channels only

