

Humpback Container



QUALITY, DURABILITY, VALUE

Standard Specifications

- Single Wall Plastic Lids.
- 14 GA construction with flanged corners and horizontal "V" groove ribs front, back and bottom.
- 12 GA bottom.
- 12 GA interlocking banding
- 11 GA 4"x 8" gusseted fork channels reinforced at pick-up points (also available flush to front). 4, 5, 6 cu yd with 11 GA channels including 6 gussets per channel and 7, 8 cu yd with 11 GA channels including 8 gussets per channel.
- Zinc plated lid rod with 90 degree bend and nylon lock nut.
- Lid ears to accommodate plastic or steel lids.
- 16" Inseam weld.
- 1 1/2" Drain plug, right side bottom centered.
- Bottom skids with end caps - 4, 5, 6, 7 cu yd with 2-12 GA formed skids and 8 cu yd with 2-7 GA formed skids @ 48" on center.
- Interior coated with automotive underseal or rust inhibitive alkyd primer.
- Exterior (including bottom) painted your choice of standard color with alkyd enamel paint. Some colors may be extra.

Humpback Container



Dimensions and Drawing

PRODUCT #	SIZE	A	B	C	D	E
11520	4 YD	72"	54"	42"	55"	41.5"
9112	5 YD	72"	66"	42"	57"	41.5"
9108	6 YD	72"	66"	50"	69"	41.5"
10073	7 YD	72"	72"	55"	73"	50.5"
9107	8 YD	72"	72"	56"	89"	50.5"

