

## Standard Rectangular Roll-Off Container



### STRONG, RUGGED, RELIABLE

#### Standard Specifications

- Horizontal "V" ribs on 12" centerlines.
- 3" X 3" (10 GA) structural tubing top headers and floor sills (no water traps).
- "Dog House" style hook-up with heavy duty snatch hook.
- 4" X 6" Nose rollers with grease fittings and 1 1/2" axles.
- 6" Structural channel gusseted main rails.
- 12 GA double doors with 1" lock bars and door header (1' taller than sides).
- Safety chain with hooks for holding doors open.
- 2" X 3" Structural tubing door hinge posts.
- 3" Structural channel floor members with 24" centerlines.
- Formed side posts with 24" centerlines.
- Tarp hooks between every other post (12" above floor).
- Formed ladder with gussets for added strength. OSHA compliant.
- Mitered corners to protect tarps.
- Gusseted front corners for strength.
- 10" X 8" Stationary steel wheels with grease fittings. Stands also available.
- Roll-off interior and exterior coated with rust inhibitive alkyd primer.
- Roll-off exterior painted your choice of standard color with alkyd enamel paint. Some colors may be extra.
- Bottom coated with automotive underseal.

## Standard Rectangular Roll-Off Container



### Dimensions

SIZE	CUBIC YDS	SIZE	CUBIC YDS
14x2	7.64	20x2	10.97
14x3	11.46	20x3	16.46
14x4	15.28	20x4	21.94
14x5	19.1	20x5	27.43
14x6	22.92	20x6	32.92
14x7	26.74	20x7	38.4
14x8	30.56	20x8	43.89
16x2	8.75	22x2	12.08
16x3	13.13	22x3	18.13
16x4	17.5	22x4	24.17
16x5	21.88	22x5	30.21
16x6	26.25	22x6	36.25
16x7	30.63	22x6.5	39.27
16x8	35	22x7	42.29
		22x8	48.33
18x2	9.86		
18x3	14.79	24x2	13.19
18x4	19.72	24x3	19.79
18x5	24.65	24x4	26.39
18x6	29.58	24x5	32.99
18x7	34.51	24x6	39.58
18x8	39.44	24x7	46.18
		24x8	52.78